



HYDRO-BIOS

Smart Sampling

Datasheet Free Flow 1 l (436 340)



Free Flow Water Sampler 1 l

Free-flushing oceanographic water sampler

The Free Flow Water Sampler is an innovative design which avoids the limitations of the PWS/Niskin bottles caused by their reduced inlet and outlet diameters. The outstanding feature of the Free Flow Water Sampler is the really free-flushing construction of the sampler where no cone or ball-valve influences the water exchange inside the sampling tube.

The Free Flow Water Sampler features all plastic (PVC and POM) design, consisting of a tube with two lids connected by a latex rubber tubing. The lids are kept open during descent, caring for a perfect flushing of the sampling tube. Like the PWS, the Free Flow Water Sampler on the one hand can be used on Multi Water Sampler/ Rosette/ Carousel arrays and on the other hand it can be used as single or series instrument connected to a hydrographic wire. When used directly connected to a hydrographic wire, a messenger (not incl.), dropped down the wire from the surface, releases the end stoppers for closure. For the use of several Free Flow Water Samplers in a row a second messenger below the first sampler is used to actuate a series of samplers along the wire.

When operated as a single instrument without bottom weight, we recommend to use a Centered Mounting Rack (436 380) which cares for a vertical position of the sampler. Retrieve the water sample via the discharge cock/tube at the lower end of the sampler.



TECHNICAL DETAILS

length	515 mm (C)
width	165 mm (A)
height	140 mm (B)
diameter	90 mm (D)
sample volume	1 l
weight on air	3 kg (empty)
operational temperature	-2 to +60 °C
product ID	436 340

CHARACTERISTICS

■ **free-flushing construction**

■ **innovative design**